

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
10 February 2005 (10.02.2005)

PCT

(10) International Publication Number
WO 2005/012830 A2

(51) International Patent Classification⁷: **G01B 7/00**

(21) International Application Number:
PCT/JP2004/011107

(22) International Filing Date: 28 July 2004 (28.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003-204374 31 July 2003 (31.07.2003) JP

(71) Applicant (for all designated States except US): **YAZAKI CORPORATION** [JP/JP]; 4-28, Mita 1-chome, Minato-ku, Tokyo 108-8333 (JP).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **SAWAI, Masayoshi** [JP/JP]; c/o Yazaki Parts Co., Ltd., 2464-48, Washizu, Kotsai-shi, Shizuoka 431-0431 (JP).


(74) Agents: **OGURI, Shohei** et al.; Eikoh Patent Office, 13th Floor, ARK Mori Building, 12-32, Akasaka 1-chome, Minato-ku, Tokyo 107-6013 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: ROTATION ANGLE CALCULATING METHOD OF WIRE HARNESS, ROTATION ANGLE CALCULATING APPARATUS, AND COMPUTER-READABLE RECORDING MEDIUM



(57) Abstract: In a rotation angle calculating method of a wire harness, a rotation angle of the wire harness is calculated at an arbitrary measuring point of the wire harness when the wire harness is deformed from a first shape to a second shape while a fixed point of the wire harness is fixed. The method includes the steps of: setting intermediate points between the fixed point and the measuring point of the wire harness in the second shape; setting vectors at the nodes of the wire harness in the second shape as node vectors respectively; calculating angles, each of which has a rotation direction, wherein each of the angles is defined between the vectors at the adjoining nodes; and adding the angles to each other so as to calculate a rotation angle having a rotation direction at the measuring point.



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *without international search report and to be republished upon receipt of that report*